

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A wood wall construction made from wooden beams, ~~comprising the wooden beams are superposed or juxtaposed~~ stacked one on top of the other and assembled using screws, which are screwed from an upper or a lower side of two wooden beams into a mutual attachment area bridging the two wooden beams and which extend only over a part of a height or thickness of each of the wooden beams, the wooden beams (1) are connected to one another by the screws (2) which are provided with threaded sections (3, 4) at least at both end sections thereof, with the screws being screwed-in without pre-drilling the wooden beams and which engage only immediately adjacent to a mutual attachment area (5) of the two wooden beams (1), with a length (C) of the screws (2) being smaller than a height (B) of one of the wooden beams (1).
2. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) extend approximately equally far into the adjacent contacting wooden beams (1) on both sides of the mutual attachment area (5).
3. (Previously presented) A wood wall construction according to claim 1, wherein at least two screws (2) are screwed into the mutual attachment area (5) of the two wooden beams (1) which are spaced apart from one another and aligned generally parallel to one another.

4. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are provided with a thread over an entire length of a shaft thereof.

5. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are provided with an interior tool grip (6) at one end thereof, with a diameter of a section of the screws (2) surrounding the interior tool grip (6) being approximately equal in size or slightly larger than an outside diameter of the thread.

6. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are located at edge regions of a strip-shaped sealing material arranged or inserted between the wooden beams (1) in the mutual attachment area (5).

7. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are screwed-in perpendicularly in reference to a longitudinal extension of the wooden beams (1).

8. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are screwed-in at an acute angle in reference to a longitudinal extension of the wooden beams (1).

9. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are screwed-in both perpendicular as well as at an acute angle in reference to a longitudinal extension of the wooden beams (1).

10. (Previously presented) A wood wall construction according to claim 9, wherein the screws are screwed in subsequently alternating positions.

11. (Previously presented) A wood wall construction according to claim 1, wherein the screws (2) are each screwed-in in pairs that cross one another at an acute angle in reference to one another and perpendicular to a longitudinal extension of the wooden beams (1).